



A01-PU2

WebRunner USB V.90/V.92 56K Modem

- Modem USB 56K V.92
- Hot Plug'n'Play
- Consente l'invio/ricezione di fax (G3) sino a 14.400 bps
- Design compatto ideale per notebooks e desktop

WebRunner USB è un Modem PSTN semplice da installare, facile da usare e veloce nella connessione. La comoda connessione USB, per collegare e scollegare il Modem senza spegnere il Personal, sfrutta l'alimentazione del PC. Lo standard V.92 consente una connessione rapida ignorando alcuni passaggi della sequenza di training e stabilendo la connessione più velocemente. Permette inoltre una comunicazione in upstream fino a 48Kbps. Il protocollo V.44 migliora la compressione dati fino al 30%, diminuendo i tempi di attesa.



WebRunner



WebRunner USB V.90/V.92 56K Modem

CARATTERISTICHE TECNICHE:

MODEM FEATURES

USB Interface 1.1

ITU-T V.92* Data/Fax modem

Quick Connect, Modem-on-Hold ** and 48Kbps PCM upstream supported for ITU-T V.92

Automatic detection between data/fax calls

Line quality monitoring and re-train

Enhanced ADPCM/PCM voice operation with concurrent DTMF detection

Bus Powered. Does not require any external power supply

CHIPSET SOLUTIONS

Based on ST Microelectronics Pegasus Discrete DAA chipset configuration

DATA MODE FEATURES

56Kbps Internet connectivity via ITU/TIA V.92 standard

DTE rate of up to 460,800 bps (via Virtual UART)

DATA MODEM STANDARD

V.90/V.92 : 56Kbps

K56flex™: 56Kbps

V.34bis: 33.6Kbps

V.34:28.8Kbps

V.32bis: 14.4Kbps

V.32, V.23, V.22bis, V.22, V.21

Bell 103 and Bell 212A

DATA COMPRESSION

V.44

V.42bis, MNP 5

ERROR CORRECTION

V.42, LAPM, MNP 2-4

FAX MODULATIONS

V.17:14.4Kbps

V.29:9,600 bps

V.27ter:4,800 bps

FAX CONTROL/ PROTOCOL

Class 1, V.21 Channel 2

Group 3 fax mode

USB FEATURES

Complies with USB Specifications rev1.1

Complies with USB COM Class rev 1.1

Complies with USB Data Class rev 1.1

Supports Suspend/Resume

Bus Powered, does not require external power supply

OnNow Power Management (D0, D2, D3)

DRIVERS SUPPORT

Windows®98SE, Windows®2000, Windows®Millennium, Windows®XP

Linux [Kernel 2.4 and 2.6]

OPERATING ENVIRONMENT

Operating temperature: 5°C ~ 40°C

Storage temperature: -25°C ~ 50°C

Humidity: 5% ~ 95% non-condensing

MINIMUM SYSTEM REQUIREMENTS

Pentium® MMX 233MHz with 128MB RAM for Windows® 2000 / Windows® XP

A free USB Port

A CDROM Drive

PACKAGE CONTENTS

WebRunner USB V.90/V.92 56K Modem

Installation CD

Telephone Extension Cable RJ-11

Quick Start Manual

* V.92 feature is subjected to ISP support

** requires software application support

All rights registered

Microsoft and Windows are registered trademarks of Microsoft Corporation

All trade names and marks are registered trademarks of respective companies

Specifications are subjected to change without prior notice. No liability for technical errors and/or omissions

Telephone line conditions may limit your ability to connect at the highest speed

PRODOTTO: WebRunner USB
CODICE: A01-PU2
CODICE EAN: 8026974001050